



FLEXDRUM HUB SPECIFICATION CHART

	82-B	121-B	141-B	840-B
Diameter of Finished Wheel	8"	12"	14" or 16"	16" or 18"
Diameter of Hub Alone	2-3/8"	4"	6"	8"
Arbor Hole	1" or 5/8-11" thd	3/4" to 1-3/4"	1" to 3-1/2"	1-1/4" to 5"
Segments	12	20	30	40



HOW TO DETERMINE SIZE OF FINISHED FLEXDRUM

HUB DIAMETER	+	TRIM LENGTH (X2)	=	FINISHED WHEEL
2-3/8"		2-3/4"		8"
4"		4"		12"
4"		5"		14"
6"		4"		14"
6"		5"		16"
8"		4"		16"
8"		5"		18"



PLAIN

**Plain Segment
for flat or mildly
contoured surfaces**



1/4" SCORE

**1/4" Scored (SC)
great for complex
parts and provides
a fine finish**



1/2" SLASH

**1/2" Slash (SL)
great for mild and
moderate contours**



INTERLEAF SEGMENT

For decorative finishes



www.meritabrasives.com

U.S. CUSTOMER SERVICE:
Saint-Gobain Abrasives, Inc.
2770 West Washington Street
Stephenville, TX 76401
Telephone: 800-421-1936
Fax: 800-472-3094

CANADA CUSTOMER SERVICE:
Saint-Gobain Abrasives Canada Inc.
PO Box 3008, 3 Beach Road
Hamilton, ON L8L 7Y5
Telephone: (905) 547-2551
Fax: (905) 547-8157

© Saint-Gobain Abrasives, Inc. October 2007
The Merit Logo is a registered trademark of
Saint-Gobain Abrasives, Inc.
FORM #M103